

Locking Plate System

Product Catalogue



Table of Contents

Large Implant and Instrument Set	5.0 mm Locking Plate System	1.1
---	-----------------------------	-----

Small Implant and Instrument Set	3.5 mm Locking Plate System	2.1
---	-----------------------------	-----

Mini Implant and Instrument Set	2.4 mm Locking Plate System	3.1
--	-----------------------------	-----

	2.0 mm Locking Plate System	3.7
--	-----------------------------	-----

	1.5 mm Locking Plate System	3.10
--	-----------------------------	------

Hip Plate System	Hip Plate System	4.1
-------------------------	------------------	-----



Large Implant and Instrument Set

5.0 mm Locking Plate System

Plates

5.0 mm Locking Plate, Narrow

Profile

Thickness: 4.2 mm
 Width: 13.5 mm
 Hole spacing: 18.0 mm



Holes	Length mm	Stainless Steel	Titanium
2	44	450102A-000	450102A-200
3	62	450103A-000	450103A-200
4	80	450104A-000	450104A-200
5	98	450105A-000	450105A-200
6	116	450106A-000	450106A-200
7	134	450107A-000	450107A-200
8	152	450108A-000	450108A-200
9	170	450109A-000	450109A-200
10	188	450110A-000	450110A-200
11	206	450111A-000	450111A-200
12	224	450112A-000	450112A-200
13	242	450113A-000	450113A-200
14	260	450114A-000	450114A-200
15	278	450115A-000	450115A-200
16	296	450116A-000	450116A-200
18	332	450118A-000	450118A-200
20	368	450120A-000	450120A-200
22	404	450122A-000	450122A-200
24	440	450124A-000	450124A-200

5.0 mm Locking Plate, Broad

Profile

Thickness: 5.2 mm
 Width: 17.5 mm
 Hole spacing: 18.0 mm



Holes	Length mm	Stainless Steel	Titanium
6	116	450206A-000	450206A-200
7	134	450207A-000	450207A-200
8	152	450208A-000	450208A-200
9	170	450209A-000	450209A-200
10	186	450210A-000	450210A-200
11	206	450211A-000	450211A-200
12	229	450212A-000	450212A-200
13	242	450213A-000	450213A-200
14	260	450214A-000	450214A-200
15	278	450215A-000	450215A-200
16	296	450216A-000	450216A-200
17	314	450217A-000	450217A-200
18	332	450218A-000	450218A-200
20	368	450220A-000	450220A-200
22	404	450222A-000	450222A-200
24	440	450224A-000	450224A-200

Plates

5.0 mm Locking Lateral Proximal Tibial Plate



Holes	Direction	Length mm	Stainless Steel	Titanium
4	R	82	450304A-000	450304A-200
4	L	82	450304B-000	450304B-200
6	R	118	450306A-000	450306A-200
6	L	118	450306B-000	450306B-200
8	R	154	450308A-000	450308A-200
8	L	154	450308B-000	450308B-200
10	R	190	450310A-000	450310A-200
10	L	190	450310B-000	450310B-200
12	R	226	450312A-000	450312A-200
12	L	226	450312B-000	450312B-200
14	R	262	450314A-000	450314A-200
14	L	262	450314B-000	450314B-200

5.0 mm Locking Medial Proximal Tibial Plate



Holes	Direction	Length mm	Stainless Steel	Titanium
4	R	106	450404A-000	450404A-200
4	L	106	450404B-000	450404B-200
6	R	142	450406A-000	450406A-200
6	L	142	450406B-000	450406B-200
8	R	178	450408A-000	450408A-200
8	L	178	450408B-000	450408B-200
10	R	214	450410A-000	450410A-200
10	L	214	450410B-000	450410B-200
12	R	250	450412A-000	450412A-200
12	L	250	450412B-000	450412B-200
14	R	286	450414A-000	450414A-200
14	L	286	450414B-000	450414B-200
16	R	322	450416A-000	450416A-200
16	L	322	450416B-000	450416B-200

5.0 mm Locking Distal Femur Plate



5.0 mm Locking
Plate System

Holes	Direction	Length mm	Stainless Steel	Titanium
5	R	156	450605A-000	450605A-100
5	L	156	450605B-000	450605B-100
7	R	196	450607A-000	450607A-100
7	L	196	450607B-000	450607B-100
9	R	236	450609A-000	450609A-100
9	L	236	450609B-000	450609B-100
11	R	276	450611A-000	450611A-100
11	L	276	450611B-000	450611B-100
13	R	316	450613A-000	450613A-100
13	L	316	450613B-000	450613B-100

Screws

4.5 mm Cortex Screw with Hexalobular Socket, Self-tapping



Profile

Thread diameter:	4.5 mm
Drill bit for threaded hole:	3.2 mm
Drill bit for gliding hole:	4.5 mm
Core diameter:	3.0 mm
Head diameter :	8.0 mm
Hexalobular socket :	T25

Length mm	Stainless Steel	Titanium
12	257012E-000	257012E-100
14	257014E-000	257014E-100
16	257016E-000	257016E-100
18	257018E-000	257018E-100
20	257020E-000	257020E-100
22	257022E-000	257022E-100
24	257024E-000	257024E-100
26	257026E-000	257026E-100
28	257028E-000	257028E-100
30	257030E-000	257030E-100
32	257032E-000	257032E-100
34	257034E-000	257034E-100
36	257036E-000	257036E-100
38	257038E-000	257038E-100
40	257040E-000	257040E-100
42	257042E-000	257042E-100
44	257044E-000	257044E-100
46	257046E-000	257046E-100
48	257048E-000	257048E-100
50	257050E-000	257050E-100
52	257052E-000	257052E-100
54	257054E-000	257054E-100
56	257056E-000	257056E-100
58	257058E-000	257058E-100
60	257060E-000	257060E-100
62	257062E-000	257062E-100
64	257064E-000	257064E-100
66	257066E-000	257066E-100
68	257068E-000	257068E-100
70	257070E-000	257070E-100
72	257072E-000	257072E-100
74	257074E-000	257074E-100
76	257076E-000	257076E-100
80	257080E-000	257080E-100
85	257085E-000	257085E-100
90	257090E-000	257090E-100
95	257095E-000	257095E-100
100	257100E-000	257100E-100
105	257105E-000	257105E-100
110	257110E-000	257110E-100
115	257115E-000	257115E-100
120	257120E-000	257120E-100
125	257125E-000	257125E-100
130	257130E-000	257130E-100
135	257135E-000	257135E-100
140	257140E-000	257140E-100
145	257145E-000	257145E-100
150	257150E-000	257150E-100
155	257155E-000	257155E-100
160	257160E-000	257160E-100

5.0 mm Locking Screw with Hexalobular Socket, Self-tapping



Profile	
Thread diameter:	5.0 mm
Drill bit for threaded hole:	4.3 mm
Core diameter :	4.4 mm
Hexalobular socket :	T25

Length mm	Stainless Steel	Titanium
14	239014E-000	239014E-100
16	239016E-000	239016E-100
18	239018E-000	239018E-100
20	239020E-000	239020E-100
22	239022E-000	239022E-100
24	239024E-000	239024E-100
26	239026E-000	239026E-100
28	239028E-000	239028E-100
30	239030E-000	239030E-100
32	239032E-000	239032E-100
34	239034E-000	239034E-100
36	239036E-000	239036E-100
38	239038E-000	239038E-100
40	239040E-000	239040E-100
42	239042E-000	239042E-100
44	239044E-000	239044E-100
46	239046E-000	239046E-100
48	239048E-000	239048E-100
50	239050E-000	239050E-100
52	239052E-000	239052E-100
54	239054E-000	239054E-100
55	239055E-000	239055E-100
56	239056E-000	239056E-100
58	239058E-000	239058E-100
60	239060E-000	239060E-100
65	239065E-000	239065E-100
70	239070E-000	239070E-100
75	239075E-000	239075E-100
80	239080E-000	239080E-100
85	239085E-000	239085E-100
90	239090E-000	239090E-100

Instruments

302001A-500 Drill bit, 3.2 mm dia., length 145 mm,
for AO/ASIF quick coupling



302001B-500 Drill bit, 3.2 mm dia., length 220 mm,
for AO/ASIF quick coupling



301001A-500 Drill bit, 4.3 mm dia., length 221 mm,
for AO/ASIF quick coupling



302011A-500 Drill bit, 4.5 mm dia., length 145/120 mm,
for AO/ASIF quick coupling



302002A-500 Tap for 4.5 mm dia. cortex screws,
length 125 mm, thread length 70mm



301006A-Z00 Screwdriver, hexalobular 5.0 T25,
with groove, length 240 mm



Instruments

301005A-K00 Screwdriver shaft, hexalobular 5.0 T25, short self-holding, for AO/ASIF quick coupling



303014A-Z00 Large handle with AO/ASIF quick coupling



301008A-500 Shaft for percutaneous threaded drill guide



301002B-500 Percutaneous threaded drill guide for 4.3 mm dia. drill bit



302014A-Z00 Depth gauge for 4.5-6.5 mm dia. screws



306037A-Z00 Double drill guide 4.5/3.2



5.0 mm Locking
Plate System

Instruments

301009A-Z00 Torque limiter, 4.0 Nm,
with AO/ASIF quick coupling



301007A-C00 Conical extraction screw
for 5.0 mm dia. screws





Small Implant and Instrument Set

3.5 mm Locking Plate System

Plates

3.5 mm Locking Plate

Profile

Thickness:	3.4 mm
Width:	11.0 mm
Hole spacing:	13.0 mm
Hole spacing in the plate :	13.0 mm center



Holes	Length mm	Stainless Steel	Titanium
2	33	460102A-000	460102A-200
3	46	460103A-000	460103A-200
4	59	460104A-000	460104A-200
5	72	460105A-000	460105A-200
6	85	460106A-000	460106A-200
7	98	460107A-000	460107A-200
8	111	460108A-000	460108A-200
9	124	460109A-000	460109A-200
10	137	460110A-000	460110A-200
11	150	460111A-000	460111A-200
12	163	460112A-000	460112A-200
13	176	460113A-000	460113A-200
14	189	460114A-000	460114A-200
15	202	460115A-000	460115A-200
16	215	460116A-000	460116A-200
18	228	460118A-000	460118A-200
20	241	460120A-000	460120A-200
22	254	460122A-000	460122A-200

3.5 mm One-third Tubular Plate

Profile

Thickness:	1.3 mm
Width:	9.6 mm
Hole spacing:	12.0 mm
Hole spacing in the plate :	16.0 mm center
One-third tube dia.:	11.4 mm



Holes	Length mm	Stainless Steel	Titanium
2	28	460202A-000	460202A-200
3	40	460203A-000	460203A-200
4	52	460204A-000	460204A-200
5	64	460205A-000	460205A-200
6	76	460206A-000	460206A-200
7	88	460207A-000	460207A-200
8	100	460208A-000	460208A-200
9	112	460209A-000	460209A-200
10	124	460210A-000	460210A-200
12	148	460212A-000	460212A-200

Plates

3.5 mm Locking Reconstruction Plate

Profile
 Thickness: 3.1 mm
 Width: 10.1 mm
 Hole spacing: 14.4 mm



Holes	Length mm	Stainless Steel	Titanium
4	56	460304A-000	460304A-200
5	70	460305A-000	460305A-200
6	84	460306A-000	460306A-200
7	99	460307A-000	460307A-200
8	113	460308A-000	460308A-200
9	128	460309A-000	460309A-200
10	142	460310A-000	460310A-200
11	156	460311A-000	460311A-200
12	171	460312A-000	460312A-200
13	185	460313A-000	460313A-200
14	200	460314A-000	460314A-200
16	228	460316A-000	460316A-200
18	257	460318A-000	460318A-200
20	286	460320A-000	460320A-200
22	315	460322A-000	460322A-200

3.5 mm Locking Distal Clavicle Plate



Holes	Length mm	Direction	Stainless Steel	Titanium
6/3	69	R	460503A-000	460503A-100
6/3	69	L	460503B-000	460503B-100
6/4	81	R	460504A-000	460504A-100
6/4	81	L	460504B-000	460504B-100
6/5	94	R	460505A-000	460505A-100
6/5	94	L	460505B-000	460505B-100
6/6	108	R	460506A-000	460506A-100
6/6	108	L	460506B-000	460506B-100
6/7	123	R	460507A-000	460507A-100
6/7	123	L	460507B-000	460507B-100
6/8	135	R	460508A-000	460508A-100
6/8	135	L	460508B-000	460508B-100

3.5 mm Locking Clavicle Hook Plate

Profile

Shaft Width: 11 mm

Shaft Thickness: 3.8 mm



Holes	Hook Depth mm	Direction	Stainless Steel	Titanium
4	15	R	460404A-000	460404A-100
4	15	L	460404B-000	460404B-100
4	18	R	460404C-000	460404C-100
4	18	L	460404D-000	460404D-100
5	15	R	460405A-000	460405A-100
5	15	L	460405B-000	460405B-100
5	18	R	460405C-000	460405C-100
5	18	L	460405D-000	460405D-100
6	15	R	460406A-000	460406A-100
6	15	L	460406B-000	460406B-100
6	18	R	460406C-000	460406C-100
6	18	L	460406D-000	460406D-100
7	15	R	460407A-000	460407A-100
7	15	L	460407B-000	460407B-100
7	18	R	460407C-000	460407C-100
7	18	L	460407D-000	460407D-100

3.5 mm Locking Superior Clavicle Plate



Holes	Length mm	Direction	Stainless Steel	Titanium
6	94	R	460606A-000	460606A-100
6	94	L	460606B-000	460606B-100
7	110	R	460607A-000	460607A-100
7	110	L	460607B-000	460607B-100
8	120	R	460608A-000	460608A-100
8	120	L	460608B-000	460608B-100

Plates

3.5 mm Locking Proximal Humeral Plate

Profile

Shaft width: 12.5 mm
 Shaft thickness: 3.0 mm



Holes in Shaft	Length mm	Direction	Stainless Steel	Titanium
3	90	R	460703A-000	460703A-100
3	90	L	460703B-000	460703B-100
5	114	R	460705A-000	460705A-100
5	114	L	460705B-000	460705B-100
6	161	R	460706A-000	460706A-100
6	161	L	460706B-000	460706B-100
7	178	R	460707A-000	460707A-100
7	178	L	460707B-000	460707B-100
8	196	R	460708A-000	460708A-100
8	196	L	460708B-000	460708B-100
9	214	R	460709A-000	460709A-100
9	214	L	460709B-000	460709B-100
10	231	R	460710A-000	460710A-100
10	231	L	460710B-000	460710B-100
11	249	R	460711A-000	460711A-100
11	249	L	460711B-000	460711B-100
12	267	R	460712A-000	460712A-100
12	267	L	460712B-000	460712B-100
13	285	R	460713A-000	460713A-100
13	285	L	460713B-000	460713B-100

3.5 mm Locking Lateral Distal Humeral Plate



Holes in Shaft	Length mm	Direction	Stainless Steel	Titanium
3	65	R	460903A-000	460903A-200
3	65	L	460903B-000	460903B-200
5	91	R	460905A-000	460905A-200
5	91	L	460905B-000	460905B-200
7	117	R	460907A-000	460907A-200
7	117	L	460907B-000	460907B-200
9	143	R	460909A-000	460909A-200
9	143	L	460909B-000	460909B-200
14	208	R	460914A-000	460914A-200
14	208	L	460914B-000	460914B-200

3.5 mm Medial Distal Humeral Plate



Holes in Shaft	Length mm	Direction	Stainless Steel	Titanium
3	59	R	461003A-000	461003A-200
3	59	L	461003B-000	461003B-200
5	84	R	461005A-000	461005A-200
5	84	L	461005B-000	461005B-200
7	110	R	461007A-000	461007A-200
7	110	L	461007B-000	461007B-200
9	136	R	461009A-000	461009A-200
9	136	L	461009B-000	461009B-200
14	201	R	461014A-000	461014A-200
14	201	L	461014B-000	461014B-200

3.5 mm Locking Olecranon Plate



Holes	Length mm	Direction	Stainless Steel	Titanium
2	86	R	460802A-000	460802A-200
2	86	L	460802B-000	460802B-200
4	112	R	460804A-000	460804A-200
4	112	L	460804B-000	460804B-200
6	138	R	460806A-000	460806A-200
6	138	L	460806B-000	460806B-200
8	164	R	460808A-000	460808A-200
8	164	L	460808B-000	460808B-200
10	190	R	460810A-000	460810A-200
10	190	L	460810B-000	460810B-200
12	216	R	460812A-000	460812A-200
12	216	L	460812B-000	460812B-200

Plates

3.5 mm Locking Lateral Distal Fibula Plate

Profile

Shaft width: 13.6 mm
 Shaft thickness: 3.9 mm



Holes in Shaft	Length mm	Direction	Stainless Steel	Titanium
3	73	R	461303A-000	461303A-100
3	73	L	461303B-000	461303B-100
4	86	R	461304A-000	461304A-100
4	86	L	461304B-000	461304B-100
5	99	R	461305A-000	461305A-100
5	99	L	461305B-000	461305B-100
6	112	R	461306A-000	461306A-100
6	112	L	461306B-000	461306B-100
7	125	R	461307A-000	461307A-100
7	125	L	461307B-000	461307B-100
9	151	R	461309A-000	461309A-100
9	151	L	461309B-000	461309B-100
11	177	R	461311A-000	461311A-100
11	177	L	461311B-000	461311B-100
13	203	R	461313A-000	461313A-100
13	203	L	461313B-000	461313B-100
15	229	R	461315A-000	461315A-100
15	229	L	461315B-000	461315B-100

3.5 mm Locking Medial Distal Tibial Plates

Profile

Shaft width: 13.6 mm
 Shaft thickness: 3.9 mm



Holes in Shaft	Length mm	Direction	Stainless Steel	Titanium
4	109	R	461404A-000	461404A-100
4	109	L	461404B-000	461404B-100
6	135	R	461406A-000	461406A-100
6	135	L	461406B-000	461406B-100
8	161	R	461408A-000	461408A-100
8	161	L	461408B-000	461408B-100
10	187	R	461410A-000	461410A-100
10	187	L	461410B-000	461410B-100
12	213	R	461412A-000	461412A-100
12	213	L	461412B-000	461412B-100
14	239	R	461414A-000	461414A-100
14	239	L	461414B-000	461414B-100

3.5 mm Locking Anterolateral Distal Tibia Plate



Holes in Shaft	Length mm	Direction	Stainless Steel	Titanium
5	80	R	461205A-000	461205A-200
5	80	L	461205B-000	461205B-200
7	106	R	461207A-000	461207A-200
7	106	L	461207B-000	461207B-200
9	132	R	461209A-000	461209A-200
9	132	L	461209B-000	461209B-200
11	158	R	461211A-000	461211A-200
11	158	L	461211B-000	461211B-200
13	184	R	461213A-000	461213A-200
13	184	L	461213B-000	461213B-200
15	210	R	461215A-000	461215A-200
15	210	L	461215B-000	461215B-200
17	236	R	461217A-000	461217A-200
17	236	L	461217B-000	461217B-200
19	262	R	461219A-000	461219A-200
19	262	L	461219B-000	461219B-200
21	288	R	461221A-000	461221A-200
21	288	L	461221B-000	461221B-200

3.5 mm Locking Calcaneal Plate



Holes	Length mm	Direction	Stainless Steel	Titanium
14	61	R	461501A-000	461501A-200
14	61	L	461501B-000	461501B-200
14	70	R	461502A-000	461502A-200
14	70	L	461502B-000	461502B-200

Screws

3.5 mm Cortex Screw, Hexalobular Socket, Self-tapping



Profile

Thread diameter:	3.5 mm
Drill bit for threaded hole:	2.5 mm
Drill bit for gliding hole:	3.5 mm
Core diameter:	2.4 mm
Head diameter :	6.0 mm
Hexalobular socket :	T15

Length mm	Stainless Steel	Titanium
10	255010E-000	255010E-100
12	255012E-000	255012E-100
14	255014E-000	255014E-100
16	255016E-000	255016E-100
18	255018E-000	255018E-100
20	255020E-000	255020E-100
22	255022E-000	255022E-100
24	255024E-000	255024E-100
26	255026E-000	255026E-100
28	255028E-000	255028E-100
30	255030E-000	255030E-100
32	255032E-000	255032E-100
34	255034E-000	255034E-100
36	255036E-000	255036E-100
38	255038E-000	255038E-100
40	255040E-000	255040E-100
42	255042E-000	255042E-100
44	255044E-000	255044E-100
45	255045E-000	255045E-100
46	255046E-000	255046E-100
48	255048E-000	255048E-100
50	255050E-000	255050E-100
52	255052E-000	255052E-100
54	255054E-000	255054E-100
55	255055E-000	255055E-100
56	255056E-000	255056E-100
58	255058E-000	255058E-100
60	255060E-000	255060E-100
65	255065E-000	255065E-100
70	255070E-000	255070E-100
75	255075E-000	255075E-100
80	255080E-000	255080E-100
85	255085E-000	255085E-100
90	255090E-000	255090E-100
95	255095E-000	255095E-100
100	255100E-000	255100E-100
105	255105E-000	255105E-100
110	255110E-000	255110E-100
115	255115E-000	255115E-100
120	255120E-000	255120E-100
125	255125E-000	255125E-100
130	255130E-000	255130E-100
135	255135E-000	255135E-100
140	255140E-000	255140E-100
145	255145E-000	255145E-100
150	255150E-000	255150E-100

3.5mm Locking Plate System

3.5 mm Locking Screws, Hexalobular Socket, Self-tapping



Profile

Thread diameter:	3.5 mm
Drill bit for threaded hole:	2.8 mm
Core diameter:	2.9 mm
Hexalobular socket :	T15

Length mm	Stainless Steel	Titanium
10	237010E-000	237010E-100
12	237012E-000	237012E-100
14	237014E-000	237014E-100
16	237016E-000	237016E-100
18	237018E-000	237018E-100
20	237020E-000	237020E-100
22	237022E-000	237022E-100
24	237024E-000	237024E-100
26	237026E-000	237026E-100
28	237028E-000	237028E-100
30	237030E-000	237030E-100
32	237032E-000	237032E-100
34	237034E-000	237034E-100
35	237035E-000	237035E-100
36	237036E-000	237036E-100
38	237038E-000	237038E-100
40	237040E-000	237040E-100
42	237042E-000	237042E-100
44	237044E-000	237044E-100
45	237045E-000	237045E-100
46	237046E-000	237046E-100
48	237048E-000	237048E-100
50	237050E-000	237050E-100
52	237052E-000	237052E-100
54	237054E-000	237054E-100
55	237055E-000	237055E-100
56	237056E-000	237056E-100
58	237058E-000	237058E-100
60	237060E-000	237060E-100
65	237065E-000	237065E-100
70	237070E-000	237070E-100
75	237075E-000	237075E-100
80	237080E-000	237080E-100
85	237085E-000	237085E-100
90	237090E-000	237090E-100
95	237095E-000	237095E-100

Instruments

303001A-500 Drill bit, 2.5 mm dia., length 110/85 mm,
for AO/ASIF quick coupling



303001B-500 Drill bit, 2.5 mm dia., length 250 mm,
for AO/ASIF quick coupling



303008A-500 Drill bit, 2.8 mm dia., length 165 mm,
for AO/ASIF quick coupling



303008B-500 Drill bit, 2.8 mm dia., length 250/95 mm,
for AO/ASIF quick coupling



303005A-500 Tap for 3.5 mm dia. cortex screws,
length 110/50 mm



303013A-Z00 Self-retaining hexalobular T15 screwdriver



Instruments

303012A-K00 Self-retaining hexalobular T15 screwdriver shaft, length 100 mm, for AO/ASIF quick coupling



303012B-K00 Self-retaining hexalobular T15 screwdriver shaft, length 250 mm, for AO/ASIF quick coupling



303014A-Z00 Large handle with AO/ASIF quick coupling



301008A-500 Shaft for percutaneous threaded drill guide



303015B-500 Percutaneous threaded drill guide for 2.8 mm dia. drill bit, long



303016B-500 Percutaneous thread drill guide for 2.8 mm dia. drill bit, short



Instruments

303003A-Z00 Depth Gauge for 2.7 to 4.0 mm dia. screws,
measuring range up to 60 mm



303004A-Z00 Double Drill Guide 3.5/2.5



303019A-Z00 Torque Limiter, 1.5 Nm, with AO/ASIF Quick
Coupling



303018A-C00 Conical extraction screw
for 3.5 mm dia. screws





Mini Implant and Instrument Set

2.4 mm Locking Plate System

Plates

2.4 mm Locking Distal Radius Plate, Juxta

Profile

Shaft width:	7.4 mm
Shaft thickness:	1.8 mm



Holes in Shaft	Length mm	Direction	Stainless Steel	Titanium
3	45	R	470203A-000	470203A-200
3	45	L	470203B-000	470203B-200
5	61	R	470205A-000	470205A-200
5	61	L	470205B-000	470205B-200

2.4 mm Locking Volar Distal Radius Plate

Profile

Shaft width:	7.4 mm
Shaft thickness:	2.0 mm



Holes head/shaft	Length mm	Direction	Stainless Steel	Titanium
6/2	45	R	470302A-000	470302A-200
6/2	45	L	470302B-000	470302B-200
6/3	54	R	470303A-000	470303A-200
6/3	54	L	470303B-000	470303B-200
6/4	66	R	470304A-000	470304A-200
6/4	66	L	470304B-000	470304B-200
6/5	75	R	470305A-000	470305A-200
6/5	75	L	470305B-000	470305B-200
6/6	85	R	470306A-000	470306A-200
6/6	85	L	470306B-000	470306B-200
7/2	45	R	471402A-000	471402A-200
7/2	45	L	471402B-000	471402B-200
7/3	54	R	471403A-000	471403A-200
7/3	54	L	471403B-000	471403B-200
7/4	66	R	471404A-000	471404A-200
7/4	66	L	471404B-000	471404B-200
7/5	75	R	471405A-000	471405A-200
7/5	75	L	471405B-000	471405B-200
7/6	85	R	471406A-000	471406A-200
7/6	85	L	471406B-000	471406B-200

Plates

2.4 mm Locking Proximal Radius Plate



Holes in Shaft	Length mm	Direction	Stainless Steel	Titanium
2	37.5	R	471202A-000	471202A-200
2	37.5	L	471202B-000	471202B-200
3	46.5	R	471203A-000	471203A-200
3	46.5	L	471203B-000	471203B-200
4	55.5	R	471204A-000	471204A-200
4	55.5	L	471204B-000	471204B-200

2.4 mm Locking Proximal Radius Neck Plate



Holes in Shaft	Length mm	Stainless Steel	Titanium
2	32	471302A-000	471302A-200
3	41	471303A-000	471303A-200
4	50	471304A-000	471304A-200

2.4 mm Cortex Screw, Hexalobular Socket, Self-tapping



Profile

Thread diameter:	2.4 mm
Drill bit for threaded hole:	1.8 mm
Drill bit for gliding hole:	2.4 mm
Core diameter:	1.7 mm
Head diameter :	4.0 mm
Hexalobular socket :	T8

Length mm	Stainless Steel	Titanium
6	253006F-000	253006F-100
7	253007F-000	253007F-100
8	253008F-000	253008F-100
9	253009F-000	253009F-100
10	253010F-000	253010F-100
11	253011F-000	253011F-100
12	253012F-000	253012F-100
13	253013F-000	253013F-100
14	253014F-000	253014F-100
15	253015F-000	253015F-100
16	253016F-000	253016F-100
18	253018F-000	253018F-100
20	253020F-000	253020F-100
22	253022F-000	253022F-100
24	253024F-000	253024F-100
26	253026F-000	253026F-100
28	253028F-000	253028F-100
30	253030F-000	253030F-100
32	253032F-000	253032F-100
34	253034F-000	253034F-100
36	253036F-000	253036F-100
38	253038F-000	253038F-100
40	253040F-000	253040F-100
42	253042F-000	253042F-100
44	253044F-000	253044F-100
46	253046F-000	253046F-100
48	253048F-000	253048F-100
50	253050F-000	253050F-100
52	253052F-000	253052F-100
54	253054F-000	253054F-100
56	253056F-000	253056F-100
58	253058F-000	253058F-100
60	253060F-000	253060F-100

Screws

2.4 mm Locking Screws, Hexalobular Socket, Self-tapping



Profile
 Thread diameter: 2.4 mm
 Drill bit for threaded hole: 1.8 mm
 Core diameter: 1.9 mm
 Hexalobular socket : T8

Length mm	Stainless Steel	Titanium
6	235006D-000	235006D-100
7	235007D-000	235007D-100
8	235008D-000	235008D-100
9	235009D-000	235009D-100
10	235010D-000	235010D-100
11	235011D-000	235011D-100
12	235012D-000	235012D-100
13	235013D-000	235013D-100
14	235014D-000	235014D-100
16	235016D-000	235016D-100
18	235018D-000	235018D-100
20	235020D-000	235020D-100
22	235022D-000	235022D-100
24	235024D-000	235024D-100
26	235026D-000	235026D-100
28	235028D-000	235028D-100
30	235030D-000	235030D-100
32	235032D-000	235032D-100
34	235034D-000	235034D-100
36	235036D-000	235036D-100
38	235038D-000	235038D-100
40	235040D-000	235040D-100
42	235042D-000	235042D-100
44	235044D-000	235044D-100
46	235046D-000	235046D-100
48	235048D-000	235048D-100
50	235050D-000	235050D-100
52	235052D-000	235052D-100
54	235054D-000	235054D-100
56	235056D-000	235056D-100
58	235058D-000	235058D-100
60	235060D-000	235060D-100

Instruments

304006A-500 Drill bit, 1.8 mm dia., length 110/95 mm, for AO/ASIF quick coupling



304007A-500 Tap for 2.4 mm cortex screws, length 100/45 mm, for AO/ASIF quick coupling




304011A-Z00 Self-retaining screwdriver with groove, hexalobular T8, length 190 mm



306027A-K00 Self-retaining hexalobular T8 screwdriver shaft, for AO/ASIF quick coupling



306020A-Z00 Handle with AO/ASIF quick coupling, length 110 mm



304018A-Z00 Torque limiter, 0.8 Nm, with AO/ASIF quick coupling



Instruments

Price
USD

304012A-Z00 Double drill guide 2.4/1.8



304009A-600 Threaded drill guide 2.4, for drill bits 1.8 mm



2.4 mm Locking
Plate System

2.0 mm Locking Plate System

Plates

2.0 mm Locking Plate

Profile

Thickness:	1.2 mm
Width:	5.4 mm
Hole spacing:	7.0 mm



Holes	Length mm	Stainless Steel	Titanium
4	31	470104A-000	470104A-200
5	38	470105A-000	470105A-200
6	45	470106A-000	470106A-200
7	52	470107A-000	470107A-200
8	59	470108A-000	470108A-200
10	73	470110A-000	470110A-200

2.0 mm Locking Y Plate

Profile

Thickness:	1.3 mm
Width:	5.0 mm
Hole spacing:	6.8 mm



Holes shaft/head	Length mm	Stainless Steel	Titanium
7/2	54	470401A-000	470401A-200

2.0 mm Locking T Plate

Profile

Thickness:	1.4 mm
Width:	5.0 mm
Hole spacing:	6.8 mm



Holes shaft/head	Length mm	Stainless Steel	Titanium
7/3	52.4	470501A-000	470501A-200

Screws

2.0 mm Cortex Screw, Hexalobular Socket, Self-tapping



Profile	
Thread diameter:	2.0 mm
Drill bit for threaded hole:	1.5 mm
Drill bit for gliding hole:	2.0 mm
Core diameter:	1.3 mm
Head diameter :	4.0 mm
Hexalobular socket :	T6

Length mm	Stainless Steel	Titanium
6	252006F-000	252006F-100
7	252007F-000	252007F-100
8	252008F-000	252008F-100
9	252009F-000	252009F-100
10	252010F-000	252010F-100
11	252011F-000	252011F-100
12	252012F-000	252012F-100
13	252013F-000	252013F-100
14	252014F-000	252014F-100
16	252016F-000	252016F-100
18	252018F-000	252018F-100
20	252020F-000	252020F-100
22	252022F-000	252022F-100
24	252024F-000	252024F-100
26	252026F-000	252026F-100
28	252028F-000	252028F-100
30	252030F-000	252030F-100
32	252032F-000	252032F-100
34	252034F-000	252034F-100
36	252036F-000	252036F-100
38	252038F-000	252038F-100
40	252040F-000	252040F-100
42	252042F-000	252042F-100
44	252044F-000	252044F-100
46	252046F-000	252046F-100

2.0 mm Locking Screw, Hexalobular Socket, Self-tapping



Profile	
Thread diameter:	2.0 mm
Drill bit for threaded hole:	1.5 mm
Core diameter:	1.4 mm
Hexalobular socket :	T6

Length mm	Stainless Steel	Titanium
6	234006D-000	234006D-100
7	234007D-000	234007D-100
8	234008D-000	234008D-100
9	234009D-000	234009D-100
10	234010D-000	234010D-100
11	234011D-000	234011D-100
12	234012D-000	234012D-100
13	234013D-000	234013D-100
14	234014D-000	234014D-100
16	234016D-000	234016D-100
18	234018D-000	234018D-100
20	234020D-000	234020D-100
22	234022D-000	234022D-100
24	234024D-000	234024D-100
26	234026D-000	234026D-100
28	234028D-000	234028D-100
30	234030D-000	234030D-100
32	234032D-000	234032D-100
34	234034D-000	234034D-100
36	234036D-000	234036D-100
38	234038D-000	234038D-100
40	234040D-000	234040D-100

Instruments

Price
USD

304005A-500 Drill bit, 1.5 mm dia., length 110/85 mm,
for AO/ASIF quick coupling



304008A-K00 Self-retaining hexalobular T6 screwdriver shaft,
for AO/ASIF quick coupling



306020A-Z00 Handle with AO/ASIF quick coupling,
length 110 mm



304010A-600 Threaded drill guide 2.0, for drill bits 1.5 mm



304013A-Z00 Double drill guide 2.0/1.5, for 2.0 mm cortex
screws



304014A-Z00 Depth gauge for 1.5 mm to 2.4 mm screws,
measuring range up to 38 mm



304019A-Z00 Torque limiter, 0.4 Nm, with AO/ASIF quick
coupling



2.0 mm Locking
Plate System

1.5 mm Locking Plate System

Plates

1.5 mm Locking Plate

Profile

Thickness:	1.1 mm
Width:	4.3 mm
Hole spacing:	5.0 mm



Holes	Length mm	Stainless Steel	Titanium
4	19	470604A-000	470604A-200
5	24	470605A-000	470605A-200
6	29	470606A-000	470606A-200
7	34	470607A-000	470607A-200
8	39	470608A-000	470608A-200
9	44	470609A-000	470609A-200
10	49	470610A-000	470610A-200
12	59	470612A-000	470612A-200

1.5 mm Locking Y Plate

Profile

Thickness:	1.1 mm
Width:	4.0 mm
Hole spacing:	5.0 mm



Holes shaft/head	Length mm	Stainless Steel	Titanium
8/2	46	470701A-000	470701A-200

1.5 mm Locking T Plate

Profile

Thickness:	1.1 mm
Width:	4.0 mm
Hole spacing:	5.0 mm



Holes shaft/head	Length mm	Stainless Steel	Titanium
8/3	44.5	470801A-000	470801A-200

1.5 mm Locking Z Plate

Profile

Thickness:	1.1 mm
------------	--------



Holes	Length mm	Stainless Steel	Titanium
9	24.9	470901A-000	470901A-200

1.5 mm Cortex Screw, Hexalobular Socket, Self-tapping



Profile

Thread diameter:	1.5 mm
Drill bit for threaded hole:	1.1 mm
Drill bit for gliding hole:	1.5 mm
Core diameter:	1.1 mm
Head diameter :	2.5 mm
Hexalobular socket :	T4

Length mm	Stainless Steel	Titanium
6	251006C-000	251006C-100
7	251007C-000	251007C-100
8	251008C-000	251008C-100
9	251009C-000	251009C-100
10	251010C-000	251010C-100
11	251011C-000	251011C-100
12	251012C-000	251012C-100
13	251013C-000	251013C-100
14	251014C-000	251014C-100
15	251015C-000	251015C-100
16	251016C-000	251016C-100
18	251018C-000	251018C-100
20	251020C-000	251020C-100
22	251022C-000	251022C-100
24	251024C-000	251024C-100

1.5 mm Locking Screw, Hexalobular Socket, Self-tapping



Profile

Thread diameter:	1.5 mm
Drill bit for threaded hole:	1.1 mm
Core diameter:	1.1 mm
Hexalobular socket :	T4

Length mm	Stainless Steel	Titanium
6	233006C-000	233006C-100
7	233007C-000	233007C-100
8	233008C-000	233008C-100
9	233009C-000	233009C-100
10	233010C-000	233010C-100
11	233011C-000	233011C-100
12	233012C-000	233012C-100
13	233013C-000	233013C-100
14	233014C-000	233014C-100
15	233015C-000	233015C-100
16	233016C-000	233016C-100
18	233018C-000	233018C-100
20	233020C-000	233020C-100
22	233022C-000	233022C-100
24	233024C-000	233024C-100

Instruments

Price
USD

304004A-500 Drill bit, 1.1 mm dia., length 65/35 mm,
for AO/ASIF quick coupling



303020A-K00 Self-retaining hexalobular T4 screwdriver shaft,
for AO/ASIF quick coupling



306020A-Z00 Handle with AO/ASIF quick coupling,
length 110 mm



304023A-600 1.5mm Locking Sleeve



304013A-Z00 Double drill guide 2.0/1.5, for 2.0 mm cortex
screws



304014A-Z00 Depth gauge for 1.5 mm to 2.4 mm screws,
measuring range up to 38 mm



304019A-Z00 Torque limiter, 0.4 Nm, with AO/ASIF quick
coupling





Hip Plate System

Hip Plate System

Plates

5.0 mm Locking Hip Plate

Profile

Thickness	5.8 mm
Width	19.0 mm
Hole spacing	16.0 mm
Outer barrel dia.	12.5 mm



Barrel Length mm	Plate Angle °	Holes	Length mm	Stainless Steel	Titanium
25	130	2	60	458102A-000	458102A-100
		3	76	458103A-000	458103A-100
		4	92	458104A-000	458104A-100
		5	108	458105A-000	458105A-100
		6	124	458106A-000	458106A-100
25	135	2	60	458202A-000	458202A-100
		3	76	458203A-000	458203A-100
		4	92	458204A-000	458204A-100
		5	108	458205A-000	458205A-100
		6	124	458206A-000	458206A-100
25	140	2	60	458302A-000	458302A-100
		3	76	458303A-000	458303A-100
		4	92	458304A-000	458304A-100
		5	108	458305A-000	458305A-100
		6	124	458306A-000	458306A-100
25	145	2	60	458402A-000	458402A-100
		3	76	458403A-000	458403A-100
		4	92	458404A-000	458404A-100
		5	108	458405A-000	458405A-100
		6	124	458406A-000	458406A-100
25	150	2	60	458502A-000	458502A-100
		3	76	458503A-000	458503A-100
		4	92	458504A-000	458504A-100
		5	108	458505A-000	458505A-100
		6	124	458506A-000	458506A-100

Plates

5.0 mm Locking Hip Plate

Barrel Length mm	Plate Angle °	Holes	Length mm	Stainless Steel	Titanium
38	130	2	60	459102A-000	459102A-100
		3	76	459103A-000	459103A-100
		4	92	459104A-000	459104A-100
		5	108	459105A-000	459105A-100
		6	124	459106A-000	459106A-100
38	135	2	60	459202A-000	459202A-100
		3	76	459203A-000	459203A-100
		4	92	459204A-000	459204A-100
		5	108	459205A-000	459205A-100
		6	124	459206A-000	459206A-100
38	140	2	60	459302A-000	459302A-100
		3	76	459303A-000	459303A-100
		4	92	459304A-000	459304A-100
		5	108	459305A-000	459305A-100
		6	124	459306A-000	459306A-100
38	145	2	60	459402A-000	459402A-100
		3	76	459403A-000	459403A-100
		4	92	459404A-000	459404A-100
		5	108	459405A-000	459405A-100
		6	124	459406A-000	459406A-100
38	150	2	60	459502A-000	459502A-100
		3	76	459503A-000	459503A-100
		4	92	459504A-000	459504A-100
		5	108	459505A-000	459505A-100
		6	124	459506A-000	459506A-100

HPS Lag Screw




Profile

Thread diameter:	12.7 mm
Thread length:	22.0 mm
Shaft Diameter:	8.0 mm

Length mm	Stainless Steel	Titanium
50	250050A-000	250050A-100
55	250055A-000	250055A-100
60	250060A-000	250060A-100
65	250065A-000	250065A-100
70	250070A-000	250070A-100
75	250075A-000	250075A-100
80	250080A-000	250080A-100
85	250085A-000	250085A-100
90	250090A-000	250090A-100
95	250095A-000	250095A-100
100	250100A-000	250100A-100
105	250105A-000	250105A-100
110	250110A-000	250110A-100
115	250115A-000	250115A-100
120	250120A-000	250120A-100
125	250125A-000	250125A-100
130	250130A-000	250130A-100
135	250135A-000	250135A-100
140	250140A-000	250140A-100
145	250145A-000	250145A-100

HPS Compression Screw



Profile

Thread diameter:	4.0 mm
Thread length:	26.0 mm
Hexagonal Socket:	3.5 mm
Hexalobular Socket:	T25

Length mm	Socket Type	Stainless Steel	Titanium
36	Hexagonal	251003A-000	251003A-100
36	Hexalobular	251003B-000	251003B-000

Instruments

302001A-500 Drill bit, 3.2 mm dia., length 145/120 mm, for AO/ASIF quick coupling



302011A-500 Drill Bit, 4.5 mm dia., length 145/120 mm, for AO/ASIF quick coupling



302002A-500 Tap for 4.5 mm dia. cortex screws, length 125 mm, thread length 70 mm



302007A-Z00 Screwdriver, hexagonal, large, with groove, length 240 mm



302003A-600 Screwdriver shaft, hexagonal, large, length 100 mm



299509E-000 Guide wire, 2.5 mm dia., with threaded tip, length 230 mm



Instruments

302004A-900 Center sleeve, short



302005A-900 Center sleeve, long



302008A-600 Coupling screw, short



302010A-600 Guide shaft



302009A-Z00 Coupling screw, long



302012A-Z00 Wrench, length 245 mm



Instruments

302024A-Z00 Impactor for one-step insertion technique,
length 260 mm



302027A-Z00 Insert for one-step insertion technique impactor



302021A-500 Drill bit, 8.0 mm dia., length 245mm




302022A-Z00 Reamer



302025A-Z00 Reamer, for plates with short barrel



302006A-600 Knurled Nut



Instruments

302023A-500 Tap, length 220 mm



302013A-Z00 Hip screw T-Handle with AO/ASIF quick coupling, length 80 mm



302026A-Z00 T-Handle with AO/ASIF quick coupling, length 80mm



302016A-Z00 Angled guide 135°



302017A-Z00 Angled guide 140°



302018A-Z00 Angled guide 145°



Instruments

302028A-900 Direct measuring device, length 200 mm



302014A-Z00 Depth gauge for 4.5-6.5 mm dia. screws



302015A-Z00 Hip drill sleeve 4.5



306012A-N00 Screw forceps, self-retaining, length 85 mm





No. 12, Kenyuan 2nd Rd., Situn District, Taichung City 40763, Taiwan
Tel: +886-4-2463-6275 Fax: +886-4-2463-6276
www.tandrymed.com